




Hi-5
5.12kWh



GET AWAY FROM LOAD SHEDDING

FEATURES

1C
Continuous Power

10
Year Warranty

50
Units Stackable

WIFI
free
monitor

- WIFI / Bluetooth available
- Short circuit protection
- Wall-mount brackets included
- Flexible remote upgrade, monitor
- Wide range inverter compatibility
- 10 year warranty, ultra safe LFP material
- Parallel up to 50 modules
- 1C rate continuous charge/discharge
- Multi protection to avoid over discharge
- Smart BMS management for longer lifespan
- Quality design for robust applications
- Fire suppression built-in, heating system optional



Model	Hi-5
Cell Type	LFP
Rated Energy	5.12kWh
Rated Capacity	100Ah
Rated Voltage	51.2V
Charge Voltage	57.2V
Max Charge/Discharge Current	100A
Discharge Peak Current	105A / 15s, 150A / 0.5s
Parallel	Up to 50 units parallelable w/o extra device needed, 256 units parallel with hub, slave battery drops offline or come back alive does not affect system running
IP Level	IP20
Dimension	438*546*165mm
Weight	49.4Kg
Communication	CAN/RS485
Compatible Inverter	Victron, Luxpower, Deye, Voltronic, SMA Goodwe, Growatt, Sofar, Solark, SRNE, Must
Humidity	5%~85% RH (No condensation)
Work Charge / Discharge Temperature	0℃ ~ +55℃ / -20℃ ~ +55℃
Dod	90%
Remote Maintenance	Flexible remote upgrade, Original firmware backup to prevent upgrade failure
Warranty *	10 year, 6000 cycles
Certification	CE UN38.3 IEC62619
Protection	Over charge/discharge/current/voltage/temperature protection Short circuit protection, Reverse connection protection Charge balance, Low SOC protection

Together
For a Blue Future

* @ 25℃, 90% Dod, 0.5C testing condition